## **PRODUCT FEATURES**

- · Field-changeable optics for ultimate customization
- · Advanced LED technology
- Modest size profile to minimize bulky appearance
- Compatible with the Monorail and Monopoint systems by Tech Lighting
- · Integrated fully dimmable LED lamp
- Protected by a 5-year warranty



Includes 9.2 watt, 647.5 delivered lumens, 2700K or 3000K, 90 CRI field replaceable LED module Dimmable with most LED compatible ELV and Triac dimmers. Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not recommend using greater than 33% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.



Clear Black Finish









Clear Black Finish

Transparent Smoke Black Finish

Clear Satin Nickel Finish

Transparent Smoke Satin Nickel Finish

To view all available finish options, please visit techlighting.com

#### ORDFRING INFORMATION

700	SYSTEM BRM	I COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
	FJ FREEJACK	<b>927</b> 90 CRI 2700K	<b>20</b> 20°	<b>05</b> 5"	C CLEAR	<b>B</b> MATTE BLACK
	MP MONOPOINT	930 90 CRI 3000K	<b>30</b> 30°	08 7.76"	<b>K</b> TRANSPARENT SMOKE	S SATIN NICKEL
	<b>MO</b> MONORAIL		<b>40</b> 40°	14 13.76"		

Note. MP includes 4 Round Flush Canopy.

Matte Black Finish option ships with Satin Nickel Stem.


4" Stem length not available on WMO System option. For custom stem lengths, please contact the Quotes Department.

700	BRM
JOB NAME	
NOTES	



## **SPECIFICATIONS**

HARDWARE MATERIAL	Metal	
SHADE MATERIAL		
NET WEIGHT	0.79 lbs	
HEIGHT	1.3in	
WIDTH	3in	
LENGTH	3in	
BEAM SPREAD		
UP LIGHT / DOWN LIGHT / BOTH?		
WET LISTED		
DAMP LISTED		
DRY LISTED	Yes	
MIN. HANGING HEIGHT	4.8in	
MAX HANGING HEIGHT	4.8in	
TOTAL CORD LENGTH		
SLOPED CEILING ADAPTABLE?	No	
GENERAL LISTING	ETL Listed	
INCLUDES		



## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP	
DELIVERED LUMENS	647.5				
WATTS	9.2				
MAX WATTAGE PER BULB	9.2W				
INPUT VOLTAGE	12V				
INFOT VOLIAGE	120V				
DIMMING TYPE*	ELV				
	Clear, Transparent Smoke :				
ССТ	2700K				
CCI	Clear, Transparent Smoke :				
	3000K				
CRI	90 CRI				
LED LIFETIME					
L70	>50000				
AVERAGE BULB HOURS	50000				
FIELD SERVICEABLE LED					
LAMP BASE	Integrated LED				
LAMP SHAPE	Integrated LED				
LAMP INCLUDED?	Υ				
WARRANTY**	5 Years				

<sup>\*</sup> Dimming information available at  $\underline{www.techlighting.com/Downloads\#dimming}$ 

# T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.		Yes	
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.	i	N/A	

 $<sup>^*</sup>$  If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

