Strikingly elegant in its simplicity, the Chara 26 Wall Sconce is a tubular design that creates a modern industrial look. Designed with a die-cast aluminum structure, powder coat finish, and stainless steel hardware for robust durability in harsh elements. Appropriate for commercial use. Available as Square or Round in three sizes.

#### Outstanding protection against the elements:

- Powder coat finish
- Stainless Steel mounting hardware
- IP65 rated

### SPECIFICATIONS

LUMENS	1286		
WATTS	11.8		
VOLTAGE	Universal 120-277V, with integral transient 2.5kV surge protection (driver)		
DIMMING	0-10, ELV, Triac		
LIGHT DISTRIBUTION	Symmetric		
OPTICS	Not applicable		
MOUNTING OPTIONS	Wall		
ADJUSTABILITY	None		
ССТ	3000K		
CRI	90+		
COLOR BINNING	3 Step		
BUG RATING	B1-U4-G0		
DARK SKY	Non-Compliant		
WET LISTED	IP65		
GENERAL LISTING	ETL		
CALIFORNIA TITLE 24	Can be used to comply with CEC 2019 Title 24 Part 6 for outdoor use. Registration with CEC Appliance Database not required.		
START TEMP	-30°C		
FIELD SERVICEABLE LED	Yes		
CONSTRUCTION	Aluminum		
HARDWARE	Stainless Steel		
FINISH	Powder Coat		
LED LIFETIME	L70: >60,000 Hours		
WARRANTY*	5 Years		
WEIGHT	4 lbs.		




CHARA 26 OUTDOOR WALL shown in black

\* Visit techlighting.com for specific warranty limitations and details.

# ORDERING INFORMATION

PRODUCT	CRI/CCT	LENGTH	FINISH	FUNCTION	VOLTAGE	DISTRIBUTION
7000WCHA	930 90 CRI, 3000K	<b>26</b> 26"	<b>B</b> BLACK	UD UPLIGHT/DOWNLIGHT	<b>UNV</b> 120V-277V	S SYMMETRIC




Chara 26 Outdoor Wall

### PHOTOMETRICS\*

#### CHARA 26 OUTDOOR WALL - 0°

Total Lumen Output:	1286
Total Power:	11.8
Luminaire Efficacy:	109
Color Temp:	3000K
CRI:	90+
BUG Rating:	B1-U4-G0



# PROJECT INFO

FIXTURE TYPE & QUANTITY

(II)

JOB NAME & INFO

NOTES

TECH LIGHTING

# VISUAL COMFORT & CO.

7400 Linder Avenue, Skokie, Illinois 60077 T 847.410.4400

@ 2020 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.

\* For latest photometrics, please visit www.techlighting.com/OUTDOOR