### **PRODUCT FEATURES**

- High-tech display head that combines simplicity with practical technology
- · Precise light beam that directs light where you want it
- Available in four on-trend finishes, aged brass (not available on twocircuit monorail), Antique Bronze, Satin Nickel and white (not available on monorail or two-circuit)
- Compatible with the Monorail and Monopoint systems by Tech Lighting
- · Lamping options are compatible with most dimmers
- Protected by a 5-year warranty. Please visit the "About Us" Page on techlighting.com for more for warranty details



#### LAMPING

Includes 12 volt 8 watt, 750.2 toal delivered lumens, 3000K, LED module. Dimmable with Low-Voltage electronic or magnetic dimmer (based on transformer). Provided with 20°, 40° and 60° beams spread lenses. The inrush current is reduced so that the Tellium LED head can be loaded to a standard 70% of the transformer's maximum rated wattage. Additionally, the dimming performance will be more stable and have a lower minimum dim level than the existing integrated LED heads.



#### ORDFRING INFORMATION

700	SYSTEM TLM	L LENGTH (A)	FINISH	LAMP
	FJ FREEJACK	<b>3</b> 3"	R AGED BRASS	-LED930 INTEGRATED LED 90 CRI 3000K 120V (T24)
	MP MONOPOINT	<b>6</b> 6"	<b>Z</b> ANTIQUE BRONZE	
	<b>MO</b> MONORAIL	<b>12</b> 12"	S SATIN NICKEL	
			<b>W</b> WHITE	

Note. MP includes 4" Round Flush Canopy. Aged Brass is not available for Two-Circuit Monorail. For custom stem lengths, please contact the Quotes Department.

700 JOB NAME	TLML _	 	
NOTES			_




# **TELLIUM LED HEAD**

# TECH LIGHTING

# **SPECIFICATIONS**

HARDWARE MATERIAL	Metal
SHADE MATERIAL	Aluminum
NET WEIGHT	1 lbs
HEIGHT	2.3in
WIDTH	3.8in
LENGTH	2.3in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	Yes
MIN. HANGING HEIGHT	12in
MAX HANGING HEIGHT	12in
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	No
GENERAL LISTING	ETL Listed
INCLUDES	



### LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		750.2		
WATTS		8		
MAX WATTAGE PER BULB		8W		
INPUT VOLTAGE		12V		
INPUT VOLTAGE		120V		
DIMMING TYPE*		ELV		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		Υ		
WARRANTY**		5 Years		

 $<sup>* \ \, \</sup>text{Dimming information available at} \, \underline{\text{www.techlighting.com/Downloads\#dimming}} \, \\$ 

## T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.	Yes		
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.	N/A		

 $<sup>^*</sup>$  If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



<sup>\*\*</sup>Visit techlighting.com for specific warranty limitations and details.